

(ORIGINAL = A3 SHEET)

CKED & APPROVED	SURVEYED & DRAFTED	QUANTITIES	SERVICES AFFECTED	S.R.A. / SURV. GEN.		SERVICES	DATUM				
				R.T.A.		TELECOM/OPTUS -T-T-T-T-T-					INNER WEST
	-	/		A.G.L / SHELL PIPELINES		GAS — G—G—G—G—	A. H. D.	_			
	DESIGNED	<u> </u>	5	SYDNEY WATER		SEWER —S—S—S—	SCALES				STANDARD DRAINAGE
	PG/DJT			TELSTRA / OPTUS		WATER				11	STANDARD DRAINAGE
ROVED FOR CONSTRUCTION	MAY 2019	INNER WEST		SYDNEY ELECTRICITY		RAILWAY -R-R-R-R-R-R-R-R-R-R-R-R-R-R-R-R-R-R-R	NTC				STANDARD SUB
	DRAWN			NOTICE OF ENTRY		ELEC. CABLES -E-E-E-E-	NIS	2 - 1 M			STANDARD SUB
	PG/DJT			KERB & GUTTER	6	OIL PIPELINES -P-P-P-P-P-		1 - 12 C		6 1	
	MAY 2019			NOTICES	DATE	STORM WATER -SW-SW-SW-		MEND DA	TE DESCRIPTION	APPROV.	
	CKED & APPROVED	ROVED FOR CONSTRUCTION			ROVED FOR CONSTRUCTION DESIGNED PG/GJT MAY 2019 DRAWN DRAWN	ROVED FOR CONSTRUCTION	Designed PG/DIT TTILECOM/OPTUS TTILECOM/OPTUS <td< td=""><td>DESIGNED PG CONSTRUCTION RT.A. TLECOM/OPTIS -T - T - T - T - T - T - T - T - T - T</td><td>ROVED FOR CONSTRUCTION DESIGNED PG/DJT DRAWN DRAWND DRAWNN DRAWN DRAWNN DRAWNN DRAWNN DRAWN DRAWNN DRAWN DRAWNN DRAWN DRAWNN DRAW</td><td>PESIGNED PG/DJT MAY 2019 PESIGNED PG/DJT PG/DJT PESIGNED PG/DJT DRWER WEST PELECON/OPTUS FOR CONSTRUCTION T-T-T-TT CAL / SHELL PIPELNES SWER CAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER CAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SWER SWER SCAL / SHELL PIPELNES SWER SWER SWER SWER SWER SWER<td>Roved For construction RTA THE conv/optus T-T-T-T- A.L./ SHEL PIPELINES A. H. D. Roved For construction PG/DJT MAY 2019 INNER WEST Striker Watter Striker Watter Striker Watter PG/DJT MAY 2019 PG/DJT Drawe Striker Watter Striker Watter Striker Watter Striker Watter Drawe Striker Watter Striker Watter Striker Watter Striker Watter Drawe Striker Watter Striker Watter Striker Watter</td></td></td<>	DESIGNED PG CONSTRUCTION RT.A. TLECOM/OPTIS -T - T - T - T - T - T - T - T - T - T	ROVED FOR CONSTRUCTION DESIGNED PG/DJT DRAWN DRAWND DRAWNN DRAWN DRAWNN DRAWNN DRAWNN DRAWN DRAWNN DRAWN DRAWNN DRAWN DRAWNN DRAW	PESIGNED PG/DJT MAY 2019 PESIGNED PG/DJT PG/DJT PESIGNED PG/DJT DRWER WEST PELECON/OPTUS FOR CONSTRUCTION T-T-T-TT CAL / SHELL PIPELNES SWER CAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER CAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SWER SCAL / SHELL PIPELNES SWER SCAL / SHELL PIPELNES SWER SWER SWER SCAL / SHELL PIPELNES SWER SWER SWER SWER SWER SWER <td>Roved For construction RTA THE conv/optus T-T-T-T- A.L./ SHEL PIPELINES A. H. D. Roved For construction PG/DJT MAY 2019 INNER WEST Striker Watter Striker Watter Striker Watter PG/DJT MAY 2019 PG/DJT Drawe Striker Watter Striker Watter Striker Watter Striker Watter Drawe Striker Watter Striker Watter Striker Watter Striker Watter Drawe Striker Watter Striker Watter Striker Watter</td>	Roved For construction RTA THE conv/optus T-T-T-T- A.L./ SHEL PIPELINES A. H. D. Roved For construction PG/DJT MAY 2019 INNER WEST Striker Watter Striker Watter Striker Watter PG/DJT MAY 2019 PG/DJT Drawe Striker Watter Striker Watter Striker Watter Striker Watter Drawe Striker Watter Striker Watter Striker Watter Striker Watter Drawe Striker Watter Striker Watter Striker Watter

THE MINIMUM GRADE OF THE LINE SHALL BE 1 IN 200. THE GRADE SHALL FALL CONTINUOUSLY TO PREVENT SILTING UP

TRENCHES SHALL HAVE CLEARLY CUT SIDES TO AVOID CONTAMINATION OF THE FILTER DURING CONSTRUCTION.

ENSURE THAT AN APPROPRIATE RECYCLED FILTER MATERIAL IS USED IN ACCORDANCE WITH TABLE ON THIS SHEET, CLASS D10 OF THE IPWEA'S SPECIFICATION FOR SUPPLY OF RECYCLED MATERIAL FOR PAVEMENTS, EARTH WORKS AND DRAINAGE. A MAXIMUM FILTER AGGREGATE SIZE OF NOMINAL 10mm SHALL BE USED TO AVOID PUNCTURING THE PIPE.

A MINIMUM 50mm LAYER OF FILTER MATERIAL SHALL FIRST BE PLACED IN THE TRENCH TO PROVIDE A DRAINAGE PATH UNDERNEATH THE PLASTIC PIPE.

THE PIPE SHALL BE KEPT IN THE CENTRE OF THE TRENCH AND THE FILTER MATERIAL COMPACTED UNDER THE HAUNCHES, AROUND THE SIDES AND ABOVE THE PIPE.

(a) AT THE UPSTREAM END PROVIDE A 90mmø UPVC RISER (SEWER GRADE) WITH A SCREWED CAP LEVEL WITH THE TOP OF KERB. PROVIDE A 90° UPVC BEND AT THE JOIN WITH THE CORRUGATED SUBSOIL PIPE. (b) AT 60m INTERVALS, AS FOR (a), BUT WITH A UPVC 'T' JUNCTION AT THE JOIN WITH THE CORRUGATED SUB SOIL

ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE

ST COUNCIL	FILE NO.	SHEET NO.	
AGE DRAWING – D8	PLAN NO.		
UBSOIL DRAINS	D8		
	VERSION	V1	